

Can I use a Windows Command Prompt to send FTP Commands to a server?

THE INFORMATION IN THIS ARTICLE APPLIES TO:

- EFT Server (All Versions)
- Secure FTP Server (All Versions)
- CuteFTP (All Versions)

QUESTION

Can I use a Windows Command Prompt to send FTP Commands to the Server?

ANSWER

Using [CuteFTP](#), you can communicate with an FTP site on the lowest possible level. You can define an FTP site in the Site Manager, then simply double-click it to connect and log in. Using CuteFTP's **Custom Commands** dialog box, you can define command sequences for common tasks, and place shortcuts for the commands on the toolbar for reuse. CuteFTP makes FTP simple; however, if you prefer to use a Windows Command Prompt, the procedure and table below will help you with some of the more common FTP tasks.

To use FTP commands at Windows command prompt

1. Open a command prompt and navigate to the folder containing the files that you want to transfer, then press ENTER. For example, type:

```
cd "C:\Documents and Settings\marsha\My Documents\CaseStudies" (You need the quotes if you have spaces in your path.)
```

2. At the **C:\>** prompt, type **FTP**. The **C:\>** prompt changes to **ftp>**.
3. At the **ftp>** prompt, type **open** followed by the name of the remote FTP site, then press ENTER. For example, type:

```
open myftpsite.com
```

4. When prompted, type the username and password provided to you by the administrator of the FTP site, then press ENTER.

Can I use a Windows Command Prompt to send FTP Commands to a server?



If you get a 10061 error, it is likely the site is refusing to accept your connection because of security privileges or because it is not an FTP server. For a list of FTP error codes, refer to Knowledge Base article [10142, FTP Status and Error Codes](#).

5. Type `cd` then the path to the remote server's directory in which you have permission to transfer files via FTP. For example, type:

```
cd M:\InetPub\EFTRoot\MySite\Usr\jbug
```

You are now ready to transfer files between your local directory and the remote directory using FTP commands such as `put` and `get`.

DOS FTP commands are slightly different than regular FTP commands. The table below lists some of the more common FTP commands as you would enter them at a Windows Command prompt. (Certain DOS commands also work in UNIX, but UNIX directories use a forward slash (/); DOS directories use a back slash (\).)



If you want to issue a command that is understood by a remote FTP server, but not by DOS, use the literal command in front of the FTP command. This command allows you to pass any request to the remote server without its being a valid DOS command.

Task	DOS Command	Notes
Change user password on a site	Literal SITE PSWD oldpassword newpassword	"Literal" sends a command line to the remote FTP connection and executes the SITE PSWD command.
Connect to the specified FTP	open [host] [port]	For example, type:

Can I use a Windows Command Prompt to send FTP Commands to a server?

host on the specified port		open myftpsite.com 21
Navigate to a different directory on remote machine	cd [directory]	For example, type: cd M:\InetPub\EFTRoot\MySite\Usr\jbug
Change to parent directory	cdup	Same as cd ..\
Changes directory on local machine	lcd [path]	For example, type lcd c:\temp.
Displays a list of files and folders in the current remote directory	dir [path] ls [directory] [localfile]	For example, type: dir M:\InetPub\EFTRoot\MySite\Usr\jbug or ls M:\InetPub\EFTRoot\MySite\Usr\jbug C:\temp\contents.txt
Creates a directory on the remote file system	mkdir [name]	For example, to create a folder into which you will upload your graphics files, type: mkdir images
Copies a file from the local to the remote computer	put [filename.ext]	To upload the file with a different name, use put oldfilename.ext newfilename.ext

Can I use a Windows Command Prompt to send FTP Commands to a server?

Copies multiple files from the local to the remote computer	<code>mput [files]</code>	Puts multiple files; *.* puts all files; *.txt puts all .txt files, my_*. * puts all files that start with my_ with any extension.
Copies a file from the remote to the local computer	<code>get [filename.ext]</code>	For example, type: <code>get dog.jpg</code>
Copies multiple files from the remote to the local computer	<code>mget [files]</code>	Gets multiple files; *.* gets all files; *.txt gets all .txt files, my_*. * gets all files that start with my_ with any extension.
Deletes a file	<code>delete [filename.ext]</code>	For example, type: <code>delete dog.jpg</code>
Renames a file	<code>rename [filename] [filename]</code>	For example, to rename a picture of your dog, Pooh Bear, type: <code>rename dog.jpg PoohBear.jpg</code>
Removes a directory on the remote computer	<code>rmdir [name]</code>	For example, type: <code>rmdir olddogpics</code>
List current working directory	<code>pwd</code>	Use when you forget which directory you are in or if you want to copy the path

Can I use a Windows Command Prompt to send FTP Commands to a server?

Close connection	bye (or quit)	Disconnect from remove FTP server
List of available commands or help for a specific command	help help [command] ? [command]	help by itself lists available FTP commands; help [command] or ? [command] provides help for the specific command
Change transfer mode to ASCII	ascii	Used for HTML and text files
Change transfer mode to binary	binary	Used for graphics, compressed files, audio clips, etc.
Displays current transfer mode (ASCII or binary)	status	Query the status of files, transfers in process, and other system information. The STAT command implemented on some FTP servers could allow a remote attacker to obtain sensitive information; therefore, it is disabled on some servers.
Enable/disable prompts	prompt	Use this command if you do not want to be prompted for each file transfer when transferring multiple files.

```
.telerik-reTable-2 { border-collapse: collapse; border: solid 0px; font-family: Tahoma; }
.telerik-reTable-2 tr.telerik-reTableHeaderRow-2 { border-width: 1.0pt 1.0pt 3.0pt 1.0pt;
margin-top: 0in; margin-right: 0in; margin-bottom: 10.0pt; margin-left: 0in; line-height:
115%; font-size: 11.0pt; font-family: "Calibri" , "sans-serif"; width: 119.7pt; border: solid
```

Can I use a Windows Command Prompt to send FTP Commands to a server?

```
white 1.0pt; border-bottom: solid white 3.0pt; background: #4F81BD; padding: 0in 5.4pt
0in 5.4pt; color: #FFFFFF; } .telerik-reTable-2 td.telerik-reTableHeaderFirstCol-2 {
border-width: 1.0pt 1.0pt 3.0pt 1.0pt; border: solid white 1.0pt; border-bottom: solid white
3.0pt; padding: 0in 5.4pt 0in 5.4pt; } .telerik-reTable-2 td.telerik-reTableHeaderLastCol-2 {
border-width: 1.0pt 1.0pt 3.0pt 1.0pt; border: solid white 1.0pt; border-bottom: solid white
3.0pt; padding: 0in 5.4pt 0in 5.4pt; } .telerik-reTable-2 td.telerik-reTableHeaderOddCol-2 {
border-width: 1.0pt 1.0pt 3.0pt 1.0pt; border: solid white 1.0pt; border-bottom: solid white
3.0pt; padding: 0in 5.4pt 0in 5.4pt; } .telerik-reTable-2 td.telerik-reTableHeaderEvenCol-2
{ border-width: 1.0pt 1.0pt 3.0pt 1.0pt; border: solid white 1.0pt; border-bottom: solid
white 3.0pt; padding: 0in 5.4pt 0in 5.4pt; } .telerik-reTable-2 tr.telerik-reTableOddRow-2 {
color: #666666; background-color: #F2F3F4; font-size: 10pt; vertical-align: top; }
.telerik-reTable-2 tr.telerik-reTableEvenRow-2 { color: #666666; background-color:
#E7EBF7; font-size: 10pt; vertical-align: top; } .telerik-reTable-2
td.telerik-reTableFirstCol-2 { margin-top: 0in; margin-right: 0in; margin-bottom: 10.0pt;
margin-left: 0in; line-height: 115%; font-size: 11.0pt; font-family: "Calibri" , "sans-serif";
width: 119.7pt; border-top: none; border-left: solid white 1.0pt; border-bottom: none;
border-right: solid white 3.0pt; background: #4F81BD; padding: 0in 5.4pt 0in 5.4pt; color:
#FFFFFF; } .telerik-reTable-2 td.telerik-reTableLastCol-2 { padding: 0in 5.4pt 0in 5.4pt; }
.telerik-reTable-2 td.telerik-reTableOddCol-2 { padding: 0in 5.4pt 0in 5.4pt; }
.telerik-reTable-2 td.telerik-reTableEvenCol-2 { padding: 0in 5.4pt 0in 5.4pt; }
.telerik-reTable-2 tr.telerik-reTableFooterRow-2 { color: #666666; background-color:
#FFFFFF; font-size: 10pt; vertical-align: top; padding: 0in 5.4pt 0in 5.4pt; }
.telerik-reTable-2 td.telerik-reTableFooterFirstCol-2 { margin-top: 0in; margin-right: 0in;
margin-bottom: 10.0pt; margin-left: 0in; line-height: 115%; font-size: 11.0pt; font-family:
"Calibri" , "sans-serif"; width: 119.7pt; border-top: none; border-left: solid white 1.0pt;
border-bottom: none; border-right: solid white 3.0pt; background: #4F81BD; padding: 0in
5.4pt 0in 5.4pt; color: #FFFFFF; } .telerik-reTable-2 td.telerik-reTableFooterLastCol-2 {
padding: 0in 5.4pt 0in 5.4pt; } .telerik-reTable-2 td.telerik-reTableFooterOddCol-2 {
padding: 0in 5.4pt 0in 5.4pt; } .telerik-reTable-2 td.telerik-reTableFooterEvenCol-2 {
padding: 0in 5.4pt 0in 5.4pt; }
```

GlobalSCAPE Knowledge Base

<https://kb.globalscape.com/Knowledgebase/10407/Can-I-use-a-Windows-Command-...>