

## Controlling the filename and frequency for creation of a new PGP log file

### THE INFORMATION IN THIS ARTICLE APPLIES TO:

- EFT Server Enterprise version 6.4 and later
- EFT v8 and later uses the AdvancedProperties.json file instead of the registry.

When you upgrade from EFT v7.4.x to EFT v8, the non-default settings that you have defined in the registry will be added to the Advanced Properties file during upgrade. (Default settings become part of the EFT configuration files.) For a more on how to use advanced properties, and a spreadsheet of the advanced properties, please refer to the "Advanced Properties" topic in the help for your version of EFT.

### DISCUSSION

EFT Server can log PGP operations using the advanced property below.

#### In EFT v8 and later:

Add the name:value pair to the AdvancedProperties.JSON file in EFT's \ProgramData\ directory as described in the "Advanced Properties" topic in the online help for your version of EFT.

```
{  
"PGPLogSuffixTemplate": %Y%m%d  
}
```

#### In versions prior to v8.0:

**32-bit:** HKEY\_LOCAL\_MACHINE\Software\GlobalSCAPE Inc.\EFT Server 4.0

**64-bit:** HKEY\_LOCAL\_MACHINE\SOFTWARE\Wow6432Node\GlobalSCAPE Inc.\EFT Server 4.0

Create the String: PGPLogSuffixTemplate

If the string is missing a value or zero = legacy behavior.

## Controlling the filename and frequency for creation of a new PGP log file

The registry value should contain a date-time template that is converted to the current time/date and appended to the PGP log file name (before the extension dot, or at the end of file name if there is no extension) when each PGP operation occurs.

A reg string "%Y%m%d"(no quotes) yields a new PGP log file each day with the following name: ..\ProgramData\GlobalSCAPE\EFT Server \PGPlog20110802.txt

GlobalSCAPE Knowledge Base

<https://kb.globalscape.com/Knowledgebase/10872/Controlling-the-filename-and...>