Enable or disable client logs (Advanced Property)

THE INFORMATION IN THIS ARTICLE APPLIES TO:

- EFT v8 and later

DISCUSSION

To monitor EFT client activity, you can reference EFT's log files, including the registration state of the modules, server/site functions, SFTP, SSL/TLS connections, and of course, errors and warnings. The EFT client activity log (also known as "TED6" logs) is used to log client connection information (event rules and outbound transfers), client commands/requests, remote server responses, and status messages. EFT client log files are saved in the C:\ProgramData\Globalscape\EFT Server\Logs\ folder.

The advanced property below is used to enable or disable client logs.

Add the name:value pair below to the AdvancedProperties.JSON file in the \ProgramData\ folder for EFT (for example, **C:\ProgramData\Globalscape\EFT Server**):

```
{
"EnableClientLogging":true
}
```

The default is false, meaning that logging is disabled. A value of true, enables logging.

MORE INFORMATION

This advanced property only enables or disables logging. If you want to change the format or location of the logs, that is done in the admin interface **Server > Logs** tab.

For more information about client logging, search for "EFT Client Activity Log" in the help for your version of EFT.

For more information about Advanced Properties, search for "Advanced Properties" in the help for your version of EFT.

Enable or disable client logs (Advanced Property)

For pre-v8 versions of EFT, the registry value is

SOFTWARE\Wow6432Node\GlobalSCAPE Inc.\EFT Server 7.2

GlobalSCAPE Knowledge Base
https://kb.globalscape.com/Knowledgebase/11629/Enable-or-disable-client-log...